

HSR-186-5T/6T is a full-range two way rimless ceiling speaker consisting of 5 inch/6 inch wide-bandwidth cone driver mounted in a vented, paintable baffle made of UV resistant UL94-V0 material, without an integrated backcan for quick and easy installation.

### Key Features:-

- \* 5"/6" Ceiling Speaker
- \* Equipped With Line Matching Transformer With 20/10/5 W & 30/15/7.5W Tappings respective to their models.
- \* Loud and Clear with full range speaker
- \* Input Sensitivity : Mic Input: -40dB (10mV) Line: -8dB(400mV)
- \* Easy to mount with spring brackets.
- \* Aesthetic white ABS with full white mesh grill.
- \* Aesthetic look suitable for office, gyms, school, etc.



Technical Data	HSR186-5T	HSR186-6T
Load Rating	20W	30W
Transformer Tapping	20-10-5W tapping on Transformer	30-15-7.5W tapping on Transformer
Frequency Range	70Hz-20KHz	50Hz-20KHz
SPL @ 1W/m	88dB	90dB
Speaker Driver Size	5.25inch Driver	6.25inch Driver
Impedance	8Ohm	8Ohm
Tweeter	1/2inch Mylar	1/2inch Mylar
Dimention and Depth	186(74)mm	215(80)mm
Install Dimention	161mm	190mm
Material/Colour	ABS White + Black	ABS White + Black

### Whats in the Box :-

2 x Ceiling Speaker